



Excellence in Paint

Material Safety Data Sheet

BITUSEAL

PHYSICAL PROPERTIES :

Viscosity @ 25°C	90 – 95 Krebb Units
Relative Density	1.15 kg/l
Flash Point °C, closed cup	NONE (Water based)

OTHER CHARACTERISTICS :

Group : Petroleum Asphalt

FIRE AND EXPLOSIVE HAZARDS

FLAMMABILITY: Being water based the product is non flammable. In dried form it might burn producing carbon monoxide and dioxide.

HAZARDS SYMPTOMS

INHALATION :
Sore throat, coughing
and dizziness.

SKIN :
Redness. Repeated
contact degreases
the skin leading to
irritation.

EYES :
Redness, pain.

INGESTION :
Sore throat,
abdominal pain
diarrhea, laboured
breathing.

PREVENTION

In case of insufficient
ventilation, use available
respiratory protection.

Use barrier cream and
impervious gloves.

Use face shields or
goggles. Avoid direct
contact.

Observe the rules of
hygiene. Wash hands
before eating, drinking
or smoking.

FIRE EXTINGUISHERS/ FIRST AID

Move to fresh air. In severe cases
seek medical attention .

Use hand cleaner/soap and water.
Remove contaminated clothing. If
any discomfort, get medical
attention.

Rinse immediately with plenty of
water. Seek medical advice.

Wash mouth with water. Give
plenty of water. **DO NOT
INDUCE** vomiting. Seek
medical advice.

SPILLAGE :

Keep out of sewers. Maintain high housekeeping standards. Absorb in sand or inert absorbent.

DISPOSAL :

As required by local authorities.

STORAGE :

Store in a cool place. Keep separate from oxidizers.

** Please note: More detailed safety data sheet is available on request*