Material Safety Data Sheet

ETCH PRIMER

PHYSICAL PROPERTIES :

Viscosity Ford cup no 4 (seconds)	20-25 sec
Relative Density @ 25°C	0.95 kg/l
Flash Point C, closed cup	12

OTHER CHARACTERISTICS :

Group : Combination of phenolic and poly vinyl butyrate resin incorporating inert fillers and pigments in alcohol solvent.

HAZARDS SYMPTOMS	**PREVENTION**	**FIRE EXTINGUISHERS/ FIRST AID**
FIRE : FLAMMABLE	No open flames. No smoking. No sparks.	Foam. Carbon Dioxide. Dry powder. Fog to cool and control.
EXPLOSION : Above 12 C explosive vapour-air mixtures may be formed.	Ventilation, explosion protected electrical equipment, connect to earth.	
INHALATION : Sore throat, coughing and dizziness.	In case of insufficient ventilation, use available respiratory protection.	Move to fresh air. In severe cases seek medical attention .
SKIN : Redness. Repeated contact degreases the skin leading to irritation.	Use barrier cream and impervious gloves.	Use hand cleaner/soap and water. Remove contaminated clothing. If any discomfort, get medical attention.
EYES : Redness, pain.	Use face shields or goggles. Avoid direct contact.	Rinse immediately with plenty of water. Seek medical advice.
INGESTION : Sore throat, abdominal pain diarrhea, laboured breathing.	Observe the rules of hygiene. Wash hands before eating, drinking or smoking.	Wash mouth with water. Give plenty of water. DO NOT INDUCE vomiting. Seek medical advice.

SPILLAGE :
Keep out of sewers. Maintain high housekeeping standards. Absorb in sand or inert absorbent.

DISPOSAL :
As required by local authorities.

STORAGE :
Store in a cool place and prevent any contact from any source of ignition. Keep separate from oxidizers.

**** Please note: More detailed safety data sheet is available on request***

11 Seller Road, Boksburg East 1459 | P O Box 26628, East Rand 1462
Tel: 011 914 3689/90 | Fax: 086 506 3877 | Email: office@fillritepaints.co.za
Web: www.fillritepaints.co.za