

## WOODGLOW

### Flexible Clear Coat

Modified Long Oil Alkyd

A ready for use exterior clear wood varnish exhibiting controlled moisture permeability and long term flexibility.

The advantages of using Woodglow is that no cracking or flaking will occur, therefore no loss of adhesion. The product was carefully formulated to ensure that the wood does not dry out and to accommodate movement in the wood. An insecticide and UV absorbers are included in the formulation ensuring a long lasting, easy to clean product. Product is available in a suede finish.

#### Recommended Uses

For the treatment and protection of exterior wood surfaces. A two coat application is normally recommended but very porous wood might need 3 coats.

#### Technical Data


Solvent	Turpentine
Viscosity 25°C	25 sec. (Ford cup no 4)
Washability	Excellent
SG	0.86kg/l
Accelerated stability	Pass
Practical spreading rate	10m <sup>2</sup> /l per coat
Recommended dry film	43 microns. (2 coats applied at 60 microns wet film thickness each)
Drying time	Sand dry: 2 hours
	Hard dry: 8 hours
Mass non volatile	42%
Volume non volatile	36%

#### CLEANING




Clean equipment with turps

#### SURFACE PREP



Clean the surface and sand if necessary

#### APPLICATION METHOD



Roller  
Brush  
Spray

Figures represent approximate values.