



AQUASHELL NON DRIP

Tough Elegant Sheen

Pure Acrylic Dispersion

Description

A water based emulsion paint providing a tough, UV resistant, sheen finish. The non drip structure makes application easy with minimal wastage when brush applied and no spattering when roller applied. Contains a dry film fungicide and is recommended in areas where fungal growth might occur. Even though the paint has a non drip structure it has very good flow.


Recommended Uses

As a final coat onto primed wood, metal and interior/exterior walls.

Technical Data


Fineness of grind	< 20 micron
Consistency at 23°C	Paste
Drying time:	2 hours @ 23°C
Surface Dry	5 hours @ 23°C
Recoating time	1 week
Hard Dry	0.965
Opacity (120µ)	Excellent - Conical mandrell
Flexibility	7 m ² /l per coat
Average spreading rate	85 microns
Recommended dry film	(2 coats at 120 microns wet film thickness each)
pH	8 - 9
S.G.	1.25 kg/l
Scrub Resistance	Passes Grade 1
Accelerated Stability	Pass
VOC	Very low - green product

CLEANING




Clean equipment with water

SURFACE PREP



Remove loose flaking paint
Sand, dust + clean
Apply correct primers + undercoats

APPLICATION METHOD



Roller
Brush
Spray

Figures represent approximate values.