



## **MATERIAL SAFETY DATA SHEET**

### **ACRYLIC FILLER, FIBREFILL & SKIMMING PLASTER**

#### **PHYSICAL DATA**

|                      |  |
|----------------------|--|
| Appearance:          | Off white liquid depending on inorganic / synthetic pigment                            |
| Solubility in Water: | Dispersible  |
| Chemical Group:      | Acrylic co-polymer emulsion incorporating inert fillers and pigments in water solution |
| Boiling Point:       | 100°C  |

#### **FIRE AND EXPLOSIVE HAZARDS**

**FLAMMABILITY:** Being water based the product is non-flammable. In dried form product might burn producing carbon monoxide and dioxide.

**EXTINGUISHING MEDIA:** Water, carbon dioxide or dry chemicals.

#### **HEALTH HAZARD DATA**

The product is not regarded as hazardous and for normal spillages on skin, clothing, etc, washing with water is adequate.

#### **EFFECT OF OVER-EXPOSURE**

Contact with skin: may cause irritation or rash.

Contact with eyes: may cause slight irritation or redness.

#### **EMERGENCY AND FIRST AID PROCEDURES**

For ingestion: drink water, do not induce vomiting and call for medical attention.

For skin: wash affected areas with soap and water.

For eyes: flush with copious volumes of clean water and call for immediate attention.

#### **SPILLAGES OR LEAKS**

Clean up with water before allowing to dry. Waste product should not be discharged directly into drains or waterways. Absorb spills with sand and / or rags.

**WASTE DISPOSAL METHOD**

Settled solids are normally disposed of through contractors.

**PROTECTION INFORMATION**

**PROTECTIVE EQUIPMENT:** normal protective clothing, e.g. gloves and overalls, are usually adequate. Safety glasses are recommended.

**VENTILATION:** normal conditions of ventilation are usually adequate.

**RESPIRATORY PROTECTION:** respiratory equipment is not required unless handling the product in an enclosed area.

