



Excellence in Paint

Material Safety Data Sheet

DAMPSOLVE

PHYSICAL PROPERTIES :

Viscosity Ford cup no 4 (seconds)	60 sec
Relative Density	1.44 kg/l
Flash Point C, closed cup	35

OTHER CHARACTERISTICS :

Group : Acrylic copolymer solution incorporating inert fillers and pigments in a petroleum distillate mainly of an aliphatic solvent.

HAZARDS SYMPTOMS

FIRE :
FLAMMABLE

EXPLOSION :
Above 35° C
explosive vapour-
air mixtures may be
formed.

INHALATION :
Sore throat, coughing
and dizziness.

SKIN :
Redness. Repeated
contact degreases
the skin leading to
irritation.

EYES :
Redness, pain.

INGESTION :
Sore throat,
abdominal pain
diarrhea, laboured
breathing.

PREVENTION

No open flames. No
smoking. No sparks.

Ventilation, explosion
protected electrical
equipment, connect to
earth.

In case of insufficient
ventilation, use available
respiratory protection.

Use barrier cream and
impervious gloves.

Use face shields or
goggles. Avoid direct
contact.

Observe the rules of
hygiene. Wash hand
before eating, drinking
or smoking.

FIRE EXTINGUISHERS/ FIRST AID

Foam. Carbon Dioxide. Dry
powder. Fog to cool and control.
DO NOT USE WATER JETS

Move to fresh air. In severe cases
seek medical attention .

Use hand cleaner/soap and water.
Remove contaminated clothing. If
any discomfort, get medical
attention.

Rinse immediately with plenty of
water. Seek medical advice.

Wash mouth with water.
DO NOT INDUCE vomiting
Seek medical advice.

SPILLAGE :

Keep out of sewers. Maintain high housekeeping standards. Absorb in sand or inert absorbent.

DISPOSAL :

As required by local authorities.

STORAGE :

Store in a cool place and prevent any contact from any source of ignition. Keep separate from oxidizers.