



**Excellence in Paint**

## Material Safety Data Sheet

### SOLVENT BASED FLOOR SEALER

#### PHYSICAL PROPERTIES :

Viscosity Ford cup no 4 (seconds) 25 sec 25°C  
Relative Density 0.868 kg/l  
Flash Point °C, closed cup 27

#### OTHER CHARACTERISTICS :

Group : Thermoplastic acrylic solution in aliphatic and aromatic solvent .

#### HAZARDS SYMPTOMS

FIRE :  
FLAMMABLE

EXPLOSION :  
Above 27° C  
explosive vapour-  
air mixtures may be  
formed.

INHALATION :  
Sore throat, coughing  
and dizziness.

SKIN :  
Redness. Repeated  
contact degreases  
the skin leading to  
irritation.

EYES :  
Redness, pain.

INGESTION :  
Sore throat,  
abdominal pain  
diarrhea, laboured  
breathing.

#### PREVENTION

No open flames. No  
smoking. No sparks.

Ventilation, explosion  
protected electrical  
equipment, connect to  
earth.

In case of insufficient  
ventilation, use available  
respiratory protection.

Use barrier cream and  
impervious gloves.

Use face shields or  
goggles. Avoid direct  
contact.

Observe the rules of  
hygiene. Wash hand  
before eating, drinking  
or smoking.

#### FIRE EXTINGUISHERS/ FIRST AID

Foam. Carbon Dioxide. Dry  
powder. Fog to cool and control.  
DO NOT USE WATER JETS

Move to fresh air. In severe cases  
seek medical attention .

Use hand cleaner/soap and water.  
Remove contaminated clothing. If  
any discomfort, get medical  
attention.

Rinse immediately with plenty of  
water. Seek medical advice.

Wash mouth with water.  
DO NOT INDUCE vomiting  
Seek medical advice.

**SPILLAGE :**

Keep out of sewers. Maintain high housekeeping standards. Absorb in sand or inert absorbent.

**DISPOSAL :**

As required by local authorities.

**STORAGE :**

Store in a cool place and prevent any contact from any source of ignition. Keep separate from oxidizers

