

# **Material Safety Data Sheet**

VARNISHES: EGGSHELL, GLOSS & POLYURETHANE

#### PHYSICAL PROPERTIES:

Viscosity Ford cup no 4 (seconds) 30 sec - 90 sec depending on product

Relative Density @ 25°C 0.91 kg/l Flash Point ° C, closed cup 40

# OTHER CHARACTERISTICS:

Group: Alkyd resin in a petroleum distillate mainly of an aliphatic solvent

HAZARDS SYMPTOMS	PREVENTION	FIRE EXTINGUISHERS/ FIRST AID	
FIRE: FLAMMABLE	No open flames. No smoking. No sparks.	Foam. Carbon Dioxide. Dry powder. Fog to cool and control.	
EXPLOSION: Above 40° C explosive vapourair mixtures may be formed.	Ventilation, explosion protected electrical equipment, connect to earth.		
INHALATION: Sore throat, coughing and dizziness.	In case of insufficient ventilation, use available respiratory protection.	Move to fresh air. In severe cases seek medical attention .	
SKIN: Redness. Repeated contact degreases the skin leading to irritation.	Use barrier cream and impervious gloves.	Use hand cleaner/soap and water. Remove contaminated clothing. If any discomfort, get medical attention.	
EYES : Redness, pain.	Use face shields or goggles. Avoid direct contact.	Rinse immediately with plenty of water. Seek medical advice.	
INGESTION: Sore throat, abdominal pain diarrhea, laboured breathing.	Observe the rules of hygiene. Wash hands before eating, drinking or smoking.	Wash mouth with water. Give plenty of water. DO NOT INDUCE vomiting. Seek medical advice.	

#### SPILLAGE:

Keep out of sewers. Maintain high housekeeping standards. Absorb in sand or inert absorbent.

## DISPOSAL:

As required by local authorities.

## STORAGE:

Store in a cool place and prevent any contact from any source of ignition. Keep separate from oxidizers.