

SKIMMING PLASTER

Ready for Use Skimming Plaster

Acrylic Copolymer Dispersion

Description

A ready for use skimming compound for interior and exterior surfaces. Product is water based, therefore environmental friendly and not flammable. Dries hard with good flexibility. Has excellent adhesion to all cementitious surfaces.

Recommended Uses

As a skimming compound on to raw plastered walls. Product should be applied by trowel. Can be sanded to a smooth finish with a 320 grit sandpaper. After sanding clean the surface and remove all contaminants. No undercoat is necessary as the product is properly bonded. Apply two coats of Fillrite's quality finishing premier grade paint directly to the skimming plaster. Recommended in areas where a smooth, quality finish is desired in place of gypsum based plasters.

Technical Data

Viscosity	Paste like viscosity
pH	8,5
S.G	1.4kg/l
Stability	Pass
Spreading rate /m ²	1.12 kg (0.800 lt) if applied at a thickness of 0.6mm 1.87 kg (1.340 lt) if applied at a thickness of 1 mm
Drying Time	Drying varies depending on thickness applied. If applied as above drying is approximately 2 hours.

Limitations

When applied thick (in excess of 2 mm) the product takes longer to dry.

CLEANING




Clean equipment with water

SURFACE PREP



Remove loose flaking paint
Sand, dust + clean

APPLICATION



Scraper
or
Trowel