

Fillrite

Excellence in Paint

DURAFLEX

Fine Textured Finish
Pure Acrylic Dispersion

Description

A fine textured, fibre strengthened, fully washable, matt pure acrylic emulsion paint with outstanding UV and weather resistance.

The product provides excellent adhesion to a wide variety of substrate.

Duraflex is specifically formulated for exterior walls where a textured finish is desired that does not show imperfections in the plaster.

Recommended Uses

Exterior walls, galvanised iron and wood.

Technical Data


Opacity (120 microns)	0.96 (white)
Viscosity	105 Krebb Units @ 25°C
pH	8.7
S.G.	1.4 kg/l
Scrub Resistance	Passes Grade 1
Accelerated stability (60°C)	Pass
Freeze Thaw stability	Pass
Drying Time:	45 min @ 23°C
Touch dry	2 hours @ 23 °C
Recoating time	1 week
Fully cured	7 m ² /l per coat
Average spreading rate	80 microns
Recommended dry film thickness	(2 coats at 120 microns wet film thickness each)
Flexibility	Very Good (conical mandrell)
Sheen	< 10 (85 degree head)

CLEANING




Clean equipment with water

SURFACE PREP



Remove loose flaking paint,
Sand, dust, clean
Apply correct primers

APPLICATION



Roller or Brush

Figures represent approximate values.