

FLEXCOAT

Solid Sheen Finish

Pure Acrylic Dispersion

Description

A fully washable Acrylic Sheen paint with outstanding UV and weather resistance. The high resin content provides the Flexcoat with excellent adhesion to a wide variety of substrate. Flexcoat is specifically formulated for exterior walls where water resistance and flexibility are important requirements to ensure a durable, long lasting coating.


Recommended Uses

Exterior walls, wood and galvanised iron.

Technical Data


Opacity (120 microns)	0.97 (white)
Viscosity	100 Krebb Units
pH	8.5
S.G.	1.25kg/l
Scrub Resistance	Passes grade 1
Accelerated stability (60°C)	Pass
Freeze Thaw stability	Pass
Drying Time: Touch dry	1 hour @ 23°C
Recoating time	3 hours @ 23°C
Fully cured	1 week
Average spreading rate	8 m ² /l per coat
Recommended dry film	70 microns
	(2 coats at 110 microns wet film thickness each)
Flexibility	Excellent (conical mandrell)
Sheen (85° head)	25

CLEANING




Clean equipment with water

SURFACE PREP



Remove loose flaking paint
Sand, dust + clean
Apply correct primers + undercoats

APPLICATION METHOD



Roller
Brush
Spray

Figures represent approximate values.