

UNIVERSAL ACRYLIC SHEEN

Durable Mid Sheen Finish

Pure Acrylic Dispersion

Description

A new generation pure acrylic floor and roof coating with excellent adhesion to a wide variety of substrate. This hard wearing yet flexible product is completely washable with excellent water and uv resistance.


Recommended Use

Exterior floors, Galvanised iron and tile roofs.

Technical Data


Viscosity	100 - 105 Krebb Units at 25°C
pH	8.5 - 9
S.G.	1.22kg/l
Mass non volatile	40%
Volume non volatile	28%
Scrub resistance	Passes grade 1
Accelerated stability (60°C)	Pass
Freeze thaw stability	Pass
Drying time:	Touch dry 45 min at 23°C
	Recoating time 4 hours at 23°C
	Fully cured 1 week
Practical spreading rate	Rough surface : 3m ² //coat Smooth surface : 8 m ² //coat
Recommended dry film	75 microns (2 coats at 110 microns wet film thickness each)
Flexibility	Excellent (conical mandrell)

CLEANING




Clean equipment with water

SURFACE PREP



Remove loose flaking paint
Sand, dust + clean
Apply correct primers + undercoats

APPLICATION METHOD



Roller
Brush
Spray

Figures represent approximate values.